



Low voltage & autocutter

The CT-S281 is CITIZEN's first low-voltage-operated POS printer equipped with an auto cutter.

2-Dimensional barcode

Unique in its class the CT-S281 is equipped with 2-dimensional barcode.

CT-S281

POS, Receipt printer (thermal 2 inch / 58 mm)

Applications

- Healthcare
- Hospitality
- Journal
- Kitchen
- Retail

Specifications

Model	CT-S281
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	80 mm/sec.
Print Width (maximum)	48 mm
Media Width (min to max)	58 mm
Media Thickness (min to max)	60 to 100 ?m
Media Sensor	Paper end
Main Interface	Dual Interface Serial (RS-232C), USB (version 1.1)
Power supply	100 to 240V, external power supply, Output: DC 8.5V
Reliability	100 Million pulses or 50 Km, 1 million cuts
Emulations (Languages)	ESC/POST™
Drivers and software	Free-of-charge from website, including support for various platforms
Size (W x D x H) and Weight	106x180x105 mm, 0,63 Kg + 0,24 Kg Power supply
EMC and safety standards	CE, TUV, UL, C-UL, FCC class B, VCCI

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

CT-S281

POS, Receipt printer (thermal 2 inch / 58 mm)

Features & Benefits