

L-220

METAPACE L-220

Compact desktop
label printer

Technical specifications

PRINT

Printing method	Direct thermal
Print speed	max. 152 mm/sec.
Print width	max. 56.9 mm
Print length	6 – 2,000 mm
Resolution	8 dots/mm (203 dpi) / 12 dots/mm (300 dpi) (optional)

MEDIA

Media type	Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width	15–60 mm
Roll diameter	max. 130 mm
Core diameter	12.5 – 38.1 mm
Media strength	0.06 – 0.2 mm

ELECTRONICS

Memory	Flash: 128 MB, RAM: 64 MB DDR3
Interfaces	USB 2.0, Serial, Ethernet (option), WiFi (option)
Power supply	AC 100V – 240V, DC 24V, 2,5A
Barcodes	All standard 1D and 2D Barcodes
Reliability	MCBF: min. 12 months Auto-Cutter: min. 6 months TPH: min. 6 months

SOFTWARE

Emulation	EPL (compatible), EPL II (compatible), ZPL (compatible), ZPL II (compatible), SLCS
Drivers	Windows 2000, XP, 2003 Server, Vista, Windows 7, Linux, Mac OS
Labeldesigner	Metapace Label Designer Software

SPECIFICS

Options	Auto-Cutter, Dispenser, Ethernet, WiFi
---------	--

WARRANTY

Period	24 months
--------	-----------

HOUSING

Dimensions (WxHxD)	120 × 170 × 230 mm
Weight	1.36 kg
Colour	Black, white

Highlights

- + Compact direct thermal label printer in a complete package
- + Versatile with different media
- + Print speed: 152 mm/sec.
- + Supports all common printer languages
- + Includes label design software



Drivers
by Seagull™

