

L-42T

METAPACE L-42T

Thermal transfer
label printer

Technical specifications

PRINT

Printing method	Direct thermal/Thermal transfer
Print width	max. 108 mm
Print length	6 – 1000 mm
Print speed	max. 178 mm/sec.
Resolution	8 dots/mm (203 dpi) / 12 dots/mm (300 dpi (optional))

MEDIA

Media type	Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width	25 – 116 mm
Roll diameter	max. 130 mm
Core diameter	25.4 – 38.1 mm
Media strength	0.06 – 0.2 mm

RIBBON

Ribbon width	33 – 110 mm
Ribbon length	74 m / 300 m
Core diameter	12.5 mm / 25.4 mm

ELECTRONICS

Memory	Flash: 128 MB, RAM: 64 MB DDR2
Interfaces	USB 2.0, Serial, Parallel, Ethernet (option), WiFi (option)
Power supply	AC 100V – 240V, DC 24V, 2,5A
Barcodes	All Standard 1D and 2D Barcodes
Reliability	MCBF: min. 12 months; Auto-Cutter: min. 6 months; TPH: min. 6 months

SOFTWARE

Emulation	EPL (compatible), EPL II (compatible), ZPL (compatible), ZPL II (compatible), SLCS
Drivers	Windows 2000, XP, 2003 Server, Vista, Windows 7, Linux, Mac OS
Labeldesigner	Metapace Label Designer Software

SPECIFICS

Options	Auto-Cutter, Dispenser, Ethernet, WiFi, external media holder
---------	--

WARRANTY

Period	24 months
--------	-----------

HOUSING

Dimension (WxHxD)	214 × 195 × 310 mm
Weight	2.85 kg

Highlights

- + Thermal transfer printer for professional label applications
- + Fast printing: up to 178 mm per second
- + Particularly large ribbon supply (up to 300 m)
- + Standard serial, parallel and USB interfaces
- + Complete package: power supply, label roll, transfer tape, software, and cleaning pen included



UNPACK AND
GET STARTED

Drivers
by Seagull™

