



General purpose ribbon for paper substrates

Key benefits

- Prints on a broad range of label materials from rough to smooth
- Good print darkness for perfect readability
- Suitable for all conventional large volume wax applications

Applications

- Rack identification labels
- Pallet identification labels
- Shipping labels
- Tote and crate labels
- Clothing tags
- And many more...



Recommended substrates

Rough papers	● ● ● ● ●
Coated papers/tags	● ● ● ● ●
Synthetics	● ○ ○ ○ ○

Print quality

0° barcode	● ● ● ● ●
90° barcode	● ● ○ ○ ○
Small characters	● ● ● ○ ○


Print resistance

Abrasion	● ○ ○ ○ ○
Solvent	○ ○ ○ ○ ○
Heat	60°C 140°F

Printer parameters

Maximum speed: 16 ips (400 mm/s)

Heat settings:



Technical specifications

Film thickness: 4,5µm
Total ribbon thickness: <9µm
Ink melting point: 65°C | 149°F
Coefficient of friction: Kd < 0,2
Ink blackness: 2,1 ODR
Antistatic designed

Approvals

REACH / SVHC 1907/2006/EC
EU Food Contact 1935/2004/EC
US Food Contact FDA
RoHS / Heavy Metals 2011/65/EU
California Proposition 65
Halogens IEC 61249-2-21:2003

Storage conditions

- 12 months recommended
- 20-80% Relative Humidity
- 5-35°C (40-95°F) temperature

Environmental performance

- SolFree® 100% solvent free ribbon
- Saves 365g of CO² vs standard ribbons
- French production only