



Flat Head • **Near Edge**

Wax • **Wax-Resin** • Resin

**Access** • Club • Expert • Specials



## Competitive ribbon for all labeling applications

### Key benefits

- Very good printing quality
- Prints on all label substrates
- Ideal for rough label substrates

### Applications

- Rack identification labels
- Produce labels
- Tote and crate labels
- Building material labels
- Medical device labels
- Cosmetics packaging labels
- Clothing tags
- Retail labels
- And many more...



### Recommended substrates

Rough papers	● ● ● ● ●
Coated papers/tags	● ● ● ● ●
Synthetics	● ● ● ● ○
Packaging films	● ● ● ● ○

### Print quality

0° barcode	● ● ● ● ●
90° barcode	● ● ● ● ○
Small characters	● ● ● ● ○

### Print resistance

Abrasion	● ● ● ● ○
Solvent	○ ○ ○ ○ ○
Heat	100°C   212°F

### Printer parameters

Maximum speed: 16 ips (400 mm/s)

Heat settings:



### Technical specifications

Film thickness: 4,5µm  
Total ribbon thickness: <8µm  
Ink melting point: 80°C | 176°F  
Coefficient of friction: Kd < 0,2  
Ink blackness: 1,8 ODR  
Antistatic designed

### Approvals

REACH / SVHC 1907/2006/EC  
EU Food Contact 1935/2004/EC  
US Food Contact FDA  
RoHS / Heavy Metals 2011/65/EU  
California Proposition 65

### Storage conditions

- 12 months recommended
- 20-80% Relative Humidity
- 5-35°C (40-95°F) temperature